

## 10" INDUSTRIAL TOUCHSCREEN IPC-10GB

Code: 1601889/1-I5

Size 10" | 1280\*800 | 16GB RAM | 512GB SSD

[Link to the product →](#)



### Technical data/items supplied

|                       |                                      |
|-----------------------|--------------------------------------|
| Certification         | CCC,CE, FCC ,ISO9001                 |
| Cooling system        | Fan                                  |
| Dimensions            | 185.2 x 263.2 x 42 mm                |
| Front bezel :         | Aluminum                             |
| Back housing :        | cold rolled steel plate              |
| Mounting              | Default wall mounting bracket        |
| OS support            | Microsoft ® Windows 11 PRO,64bit     |
| Weight (Net)          | 4 kg                                 |
| Weight (Gross)        | 5 kg                                 |
| Package size          | 33.5 x 26 x 9.5 (cm)                 |
| Display type          | IPS LCD screen                       |
| Display size          | 136 x 217 mm (HxV)                   |
| Resolution            | 1280 x 800                           |
| Max. colors           | 16.7 M                               |
| Luminance cd/m2       | 250                                  |
| Viewing angle (H/V°)  | 178°/178°                            |
| Backlight life        | 50000 hrs                            |
| Contrast ratio        | 800:1                                |
| Aspect ratio          | 16:10                                |
| Lifespan              | 36 million touches at single point   |
| Touch type            | 10 Point Capacitive G+G touch screen |
| Response              | ?5 ms                                |
| CPU                   | Intel® I5-3317U                      |
| Memory                | 16GB RAM                             |
| Storage               | 512GB SSD                            |
| 1x Mini PCI-E         |                                      |
| 2xCOM (RS232/485 )    |                                      |
| 1xHDMI                |                                      |
| 1xUSB 3.0             |                                      |
| 1xUSB 2.0             |                                      |
| 2xLAN (RJ-45 )        |                                      |
| 1xVGA                 |                                      |
| 1x12V DC              |                                      |
| Humidity              | 10~ 95% RH @ 40°C, non-condensing    |
| Ingress Protection    | Front panel: IP65                    |
| Operating Temperature | -10 ~ 55°C                           |

Storage Temperature -30 ~ 70°C

Adaptor (DC 12V) (cable 1 meter)

Power plug ( cable 1.2 meter )

Default wall mounting bracket

Panel cut-out: 238 x 160mm